

Proserv Flushing Unit - Offshore

Proserv offers a wide range of various flushing units with diesel-engine drive and electrical drive options for sale and hire.

We have different pump units for pure flushing or for flushing and pressure testing. We can also manufacture bespoke solutions for specific client requirements.

Features & Benefits

- Certified to ISO 4406:1999, NAS 1638 and SAE 4059D standards
- Cleanliness verification to the appropriate standard
- All stainless steel construction
- Wide range of pressure and flow combinations
- Suitable for low viscosity water and oil based fluids
- Multi voltage supply



Technical Specification

Dimensions (LxWxH)	2000 x 1000 x 1825 m
Weight	1000 kg
Engine	20 Kw
Voltage	440v/690 volt 50/60 Hz
Pump	Water, oil based and non-lubricated (for other liquids or acids please contact us)
Max discharge pressure	345 bar
Max flow rate	34 l/min @ 345 bar
Suction connection	3/4" BSP
Discharge connection	1/2" BSP
Utilities required	Water for cooling, filters : 1 HC 9800FKP8H 1 HC9100FKP8H
Standard for design	Offshore zone 1
Classification	DNV 2.7-1
Versatility	Flushing, pressure testing, injection and cleaning

ingenious simplicity

info@proserv.com

www.proserv.com